

MOBILE WORKSTATION! 5" & 8" Skid Steer Chippers!



The four-position valve easily controls the hydraulic feed roller



The chipper has two mounts, so it can be set to feed in front or to the curb side



Built-in hydraulic jack makes feed roller maintenacnce quick and easy.



Model	Hydraulics	Feed Opening Size	Chipper Capacity	Feed System	Chipper Disc	Operating Weight
CH500H (74500)	Standard or high-flow**	5.5"x7"	3"*	hydraulic	20" x 1.25" 140lbs	1145
CH800H (74800)	High-flow***	9"x9"	5"*	hydraulic	30" x 1.25" 275lbs	1525

*Continuous chipping size rating refers to the suggested feeding size of limbs for normal operation **Standard-flow requires a mimimum of 15 gallons per minute (GPM) hydraulic oil flow

***High-flow requires a minimum of 25 GPM hydraulic oil flow



Find a dealer near you! Call us at 800.247.7335 or

Log onto www.BearCatProducts.com

P.O. Box 849, West Fargo, ND 58078 Email: sales@BearCatProducts.com Fax: 701.282.9522



5" & 8" Skid Steer Specs

Models CH500H (74500), CH800H (74800)

SKID-STEER MOUNT

- CH500H (74500) fits skid steers with standard or high-flow hydraulics
- CH800H (74800) fits skid steers with high-flow hydraulics
- •Two mounts, so chipper can be mounted with feed table facing forward or to the curbside
- Easy to attach just connect chipper to the SAE J2513 Quick-Tach, attach the hydraulic hoses, and you are ready to go

HYDRAULIC FEED

- Four-position manual valve control (Reverse-Neutral-Forward-Reverse).
- Infinite speed settings with turn of a handle
- •Automatic feed control, which slows the feed roller if the disc starts to slow down

CHIPPER DISC

- •CH500H (74500) has a 20" x 1.25" [51cm x
- 3.175cm] 140lb. [63.5kg] disc. Machined.
- •CH800H (74800) has a 30" x 1.25" [76cm x 3.175cm] 275 lb. [125kg] disc. Machined & Balanced.

FOUR CHIPPING BLADES

- •Reversible heat-treated chipper steel blades, with chrome content.
- Blades are mounted 90 degrees to each other for smoother operation and less vibration.

FOUR EDGE ADJUSTABLE ANVIL/CUTTER BAR

To insure good chipping ability.

CONTINUOUS CHIPPING SIZE

- •CH500H (74500) has a 5.5" x 7" [14cm x 18cm] chipper opening for side limbs, and wil chip up to 3" limbs continuously.
- •CH800H (74800) has a 9" x 9" [23cm x 23cm] chipper opening for side limbs, and will chip up to 5" limbs continuously.

EASY ACCESS DISC

The disc is accessible through the hinged disc cover, which exposes one half of the disc for easy access to the chippping blades and for easy clean out.

INTEGRATED BLOWER

Put the chips where you want them with the dedicated blower. 360° rotating, 6" [15cm] (74500) or 8" [20cm] (74800) diameter steel tubing with adjustable deflector cap allows you to put the chips where you want them the first time.

HEAVY-DUTY CONSTRUCTION

OTHER FEATURES:

- Slip-resistant step pads for entry or exit from skid-steer
- Weatherproof owner's manual box

Weight

- Model CH500H (74500) 1145 lbs [520kg]
- Model CH800H (74800) 1525 lbs [693kg.]

Safety

- Safety chains standard
- Meets all applicable ISO and CE safety standards.



Find a dealer near you!

Call us at 800.247.7335 or Log onto www.BearCatProducts.com

> P.O. Box 849, West Fargo, ND 58078 Email: sales@BearCatProducts.com Fax: 701.282.9522